

MR2707-5

Serial No.: 10/006,124

Response to Official Action dated 13 June 2005

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions, and listing of claims in the application:

LISTING OF CLAIMS:

1. (Currently amended) An integrated speech synthesizer with an automatic identification of speaker connections comprising:
 - a sound encode register for storing encoded digitized sound data;
 - a first ~~speech-synthesis~~ digital to analog converter unit connected to said sound encode register for converting said digitized sound data from said sound encode register to a first analog signal and sending out said first analog signal through a first output terminal;
 - a second ~~speech-synthesis~~ digital to analog converter unit connected to said sound encode register for converting said digitized sound data from said sound encode register to a second analog signal and sending out said second analog signal through a second output terminal and said first output terminal; and
 - a state register connected to said first output terminal for detecting and storing a connection state of said first output terminal before said speech synthesizer is enabled, said state register having an output coupled

MR2707-5

Serial No.: 10/006,124

Response to Official Action dated 13 June 2005

to said sound encode register, said first digital to analog converter unit and said second digital to analog converter unit to thereby [[:]]
~~wherein said speech synthesizer is automatically set up with an initial value in~~
reference to said state stored in said state register for said first and
second digital to analog converters.

2. (Cancelled).

3. (Currently enabled) An integrated speech synthesizer according to claim
[[2]] 1 wherein said state register detects said first output terminal is in a high
impedance state before connected to a speaker said speech synthesizer is enabled
responsive to a speaker being coupled between said first and second output
terminals.

4. (Currently amended) An integrated speech synthesizer according to claim
[[3]] 1 wherein said state register detects said first output terminal is in a low level
and said first before said speech synthesis unit can be synthesizer is enabled when
responsive to a drive circuit for said a speaker is being connected to said first
output terminal only.

MR2707-5

Serial No.: 10/006,124

Response to Official Action dated 13 June 2005

5. (Currently amended) An integrated speech synthesizer according to claim 1 wherein said second ~~speech-synthesis~~ digital to analog converter unit is a direct drive type speech synthesis unit.

6. (Currently amended) An integrated speech synthesizer according to claim 5 wherein said second ~~speech-synthesis~~ digital to analog converter unit is a push-pull type ~~speech-synthesis~~ digital to analog converter unit.

7. (Cancelled).

8. (Currently amended) An integrated speech synthesizer according to claim [[7]] 1 wherein said second output terminal is in a high level before said speech synthesizer is enabled.

9. (Cancelled).

10. (Currently amended) A method for automatic identification of speaker connections to an integrated speech synthesizer with a ~~PCM and direct drive type~~ speech-synthesis pair of digital to analog converter units, a first of said PCM speech-synthesis pair of digital to analog converter units enable to sending out a first analog signal from a first output terminal, a second of said pair of digital to

MR2707-5

Serial No.: 10/006,124

Response to Official Action dated 13 June 2005

~~analog converter said direct drive type speech synthesis units enable to sending out~~
a second analog signal from a second output terminal and said first output
terminal, said method comprising:

setting said first output terminal to a high impedance state prior to input of
digital speech signals to said pair of digital to analog converter units;
sending out a preset voltage from said second output terminal;
detecting and storing a state of said first output terminal with a state register
having an input coupled thereto, the detection and storing step
occurring prior to said input of the digital speech signals before said
~~speech synthesizer is enabled;~~ and
setting up ~~said speech synthesizer with~~ an initial value input to said pair of
digital to analog converter units responsive to in-reference to said
detected state stored in said state register.

11. (Original) A method according to claim 10 wherein said preset voltage is high,

12. (Currently Amended) A method according to claim 10 wherein the step of
detecting and storing includes the step of setting a flag to indicate said first output
~~terminal is in a low level and said first speech synthesis unit can be enabled when~~
a drive circuit for ~~said a~~ speaker is connected to only said first output terminal

MR2707-5

Serial No.: 10/006,124

Response to Official Action dated 13 June 2005

only responsive to a low level being detected at said first output terminal prior to said input of digital speech signals.

13. (Currently amended) A method according to claim 10 wherein the step of detecting and storing includes the step of setting a flag to indicate a said first output terminal is in a high level and said direct drive type speech synthesis unit can be enabled when said speaker is connected to said first and second output terminals responsive to a high level being detected at said first output terminal prior to said input of digital speech signals.